



Nitrile



Lab & Utility

TouchNTuff®

ADVANCED PRODUCT & WORKER PROTECTION

92-600 92-605 Nitrile Glove

Proven splash resistance against hazardous chemicals

FEATURES AND BENEFITS:

Outstanding Chemical Resistance

Further testing of the TouchNTuff® by a certified body on an even wider range of chemicals confirms that it resists a greater variety of industrial chemicals for longer periods than any other nitrile disposable gloves.

Excellent puncture resistance

Manufactured from nitrile, TouchNTuff® offers up to four times the puncture resistance of comparable natural rubber latex, and three times the resistance of similar neoprene gloves.

Prevention from Type I Allergy

It contains no natural rubber latex proteins, which prevents from Type I allergies for the wearer. Primary skin irritation studies and Insult Patch tests have also shown no evidence of risk from irritation or allergic contact dermatitis.

Easy Donning and Strong Grip

With a unique “Thin Nitrile Technology” formulation, this glove offers easy donning and strong grip in wet or dry conditions. The glove is highly versatile and suitable for many different uses.



Safety5000.com®

Contract Laboratory Services Limited (T/A Safety5000)
Unit 1A Rivergreen Business Centre
Queen's Meadow Business Park
Hartlepool
Cleveland
TS25 2DL
UNITED KINGDOM

Phone: +44 (0)330 024 9933
Fax: +44 (0)330 024 9934
Website: www.safety5000.com
Email: enquiries@safety5000.com

Ansell

TECHNICAL DATA SHEET:

PRODUCT INFORMATION:

	92-600	92-605
Material	Nitrile	
Color	Green	
Glove Design	Ambidextrous, Powder Free, Smooth Grip	Ambidextrous, Powder Free, Textured Fingers
Cuff	Beaded Cuff	
Audit Standards	ISO 9001	
Quality Control	EN420, EN374/1,2,3, ASTM D 6319, FDA 21 CFR 177-2600, Arrete 09/11/04, European Regulation 1935/2004, German Recommendation for Food Commodities.	
Packaging	100 gloves per dispensers, 10 dispensers per shipper carton, 1000 gloves per shipper cartons	
Storage	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.	
Country of Origin	Sri Lanka	Thailand

PHYSICAL PROPERTIES:

PROPERTY	TYPICAL VALUES				TESTING METHOD	
SIZE	S 6½-7	M 7½-8	L 8½-9	XL 9½-10		
Length (mm)	92-600	240	240	240	ASTM D3767/EN 420	
	92-605	300	300	300		
Average Palm Width (mm)	92-600	85	96	105		
	92-605	82	90	99		
Freedom from Holes (Inspection level I)	92-600	All regions except North and South America 1.5 AQL North and South America 4.0 AQL				ASTM D5151/EN 374-2
	92-605	1.5 AQL All regions				
Palm Thickness Single Wall	(mm : 0.12) / (mils : 4.7)				ASTM D3767/EN 420	
	BEFORE AGING		AFTER AGING			
Ultimate Tensile Strength	> 14 Mpa		> 14 Mpa		ASTM D 412-06a	
Elongation at Break (%)	> 500		> 400		ASTM D 412-06a	
Force at break (N)	> 6		> 6		EN 455-2	

ORDERING INFORMATION:

	SIZE	S 6½-7	M 7½-8	L 8½-9	XL 9½-10
92-600	ASPEN US	552822	552823	552824	552825
	ORACLE US	105077	105018	105079	105080
	ASPEN OTHERS	552942	552943	552944	522945
92-605	ASPEN	588104	588105	588106	588107

(All regions except North & South America)

92-600



92-605

